

# SK-MiniS: All-In-One Live Production

Create, Switch, Stream—Anywhere, Hassle-Free



## Vizrt Ecosystem-Compatible, Portable Professional Live Production Switcher

The SK-MiniS integrates portability, multi-interface compatibility, and high-quality audio processing into a single unit. It delivers a reliable, efficient all-in-one solution for live production scenarios including on-site events, galas, small-scale competitions, and corporate live streams.



### All-In-One Workflow

Video capture, audio mixing, switching, monitoring & wireless Tally—consolidated in a portable unit. Ditch bulky gear for streamlined on-site production.



### Seamless Vizrt Sync

Works flawlessly with TriCaster series & Viz Connect Tetra. NDI-native compatibility for local/remote/cloud productions.



### Pro-Grade Connectivity

8-channel NDI input or 4x 4K HDMI/SDI (2160p30) inputs + 3x HDMI outputs. 2.5G Ethernet & dual Wi-Fi for reliable network access.



### Studio-Quality Audio

24-bit/192kHz sampling, phantom power, XLR/TRS combo inputs & built-in speakers. Perfect for commentary, music & multi-language



### Empowers real-time processing

17.3" multi-touch FHD display + built-in standard PC keyboard/trackpad, high-performance X86 architecture empowers real-time processing tasks.



### Familiar Control Layout

Instant proficiency for pros, direct "Record"/"Stream" access, real-time status feedback, and enhanced live production efficiency.

## SK-MiniS Live Production - Technical Specifications

<b>Video Input</b>	8 x Simultaneous external video inputs, supporting any combination of compatible sources in resolutions up to 2160 up to 60fps
<b>Network Video Input</b>	8 x IP video inputs via NDI, resolution-independent, with support Alpha channel
<b>Local Video Input</b>	4 x 4K HDMI/SDI Input (2160P30)
<b>Multiviewer Output</b>	<ul style="list-style-type: none"> <li>• 4 x Multiviewer outputs supporting standard display resolutions</li> <li>• 1 x 17.3 LCD Screen</li> <li>• 3 x HDMI (HDMI v2.0)</li> </ul>
<b>Local Audio I/O</b>	<ul style="list-style-type: none"> <li>• 2x XLR/TRS combo input;</li> <li>• 2x TRS balanced out;</li> <li>• 24-bit/192kHz; phantom power;</li> <li>• Headphone monitoring;</li> <li>• Built-in speakers</li> </ul>
<b>Control Panel</b>	53-Button Mini Control Panel
<b>Tally System</b>	25-Pin Red & Green Tally GPI I/O, and 433MHz RF
<b>Compatibility</b>	TriCaster Mini S Software
<b>Display</b>	17.3" LCD multi-touch (1920x1080 FHD)
<b>CPU</b>	Intel Core i9-11900H
<b>GPU</b>	RTX 3060 (12GB)
<b>RAM</b>	32GB DDR5
<b>Storage</b>	1TB NVMe SSD
<b>Input Devices</b>	Standard PC keyboard; Built-in trackpad
<b>Housing Material</b>	Aluminum Housing
<b>Dimensions</b>	418 × 290 × 76mm
<b>Operating Temperature</b>	-20°C to 60°C
<b>Power</b>	AC/DC Adapter (19V 12.3A)
<b>Weight</b>	6.8kg
<b>Warranty</b>	1-Year Warranty

Note: The Vizrt, TriCaster trademarks and logos are not owned by SanWarm and they are used for identification only.